

CS308ST



- Short throw projector
- Built-in 10W speaker
- 28dB low noise
- Bright 3600 lumens
- Versatile connectivity

Specification

Display Technology	Texas Instrument DMD, 0.55" SVGA DMD	Native Resolution	SVGA(800 x 600)
Brightness / Contrast Ratio	3600 ANSI Lumens / 22,000:1	Display Colors	1.07 billion
Projection Lens	F=2.7 ; f = 7.15mm;Fixed Lens	Image Size	31.9" to 303.09"
Projection Distance	0.4~3.8m	Throw Ratio	0.62
Digital Keystone Correction	± 20° Vertical	Aspect Ratio	4:3
Light Source Power	203W	Noise	28dB low noise
Lamp Life	6000/10000/10000/15000 (Normal/ECO/Dynamic/ECO+ Mode)	Speaker	10W
Scan Rate	Horizontal scan rate: 15.375 ~ 91.146 KHz; Vertical scan rate: 50 ~ 85 Hz	Input / Output Connections	HDMIx1, VGA-in x 1 , VGA-out x1,USB Power x1 Audio-in x1, Audio-out x1,RS232 x1
Dimensions(W x D x H)/ Weight	31.6x24.4x9.8(cm) / 2.9(kg)	Power Supply	AC 100 ~240V (50~60Hz)



Optoma Corporation
 12F., No.213, Sec. 3, Beixin Rd.,
 Xindian Dist., New Taipei City 231, Taiwan (R.O.C.)
 Tel: +886 2 8911 8600 Fax: +886 2 8911 6550
<http://www.optoma.com.tw>