

# CP- UNR-4K2162-V2

## 16 Ch. Network Video Recorder



### Main Features

- Support up to 1ch@8MP/4ch@1080P decoding
- Instastream/H.264+ codec decoding
- Up to 8MP resolution preview and playback
- Total Throughput 320Mbps
- Support 2 SATA HDDs up to 10TB Each, 2 USB ports(2.0)
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras
- ONVIF Version 2.4 conformance
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro



# CP- UNR-4K2162-V2

## 16 Ch. Network Video Recorder

### Feature

Processor  
Operating System  
IP Camera Input  
Two-way Talk  
User Interface  
Video Output  
Compression  
Encode Strategy  
Total Throughput  
Video Resolution  
Video Recording  
Video Display Split  
OSD  
Bit Rate  
Motion Detection  
Video Loss  
Camera Blank  
Smart Phone  
Hard Disk  
Trigger Events  
Recording Mode  
Search Mode  
Playback  
Backup Mode  
Interface Ports  
Record Interval  
Max User Account  
Ethernet

### Specification

Dual-core embedded processor  
Embedded LINUX  
16 channel  
1 channel Input, 1 channel Output, RCA  
GUI  
1 HDMI, 1 VGA  
H.264+  
Instastream  
320Mbps  
1920×1080, 1280×1024, 1280×720, 1024×768  
8MP/6MP/5MP/4MP/3MP/1080P/ 720P/ D1&etc.  
1/4/8/9/16  
Camera title, Time, Camera lock, Motion detection, Recording  
16Kbps ~ 20Mbps Per Channel  
MD Zones: 396(22×18).  
Supports  
Supports  
iPhone, iPad, Android Phone  
2 SATA III ports, up to 10TB Each  
Recording, PTZ, Tour, Video Push, Snapshot, and Screen Tips  
Manual, Schedule (Regular (Continuous), MD, Stop  
Time/Date, MD & Exact search (accurate to second)  
Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom  
USB Device / Network  
1 HDMI, 1 VGA, 2 USB Ports(1 Rear USB2.0, 1 Front USB2.0)  
1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec  
128 users  
1 RJ-45 port (10/100/1000Mbps)

**CP- UNR-4K2162-V2**  
16 Ch. Network Video Recorder**Feature**

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

**Specification**

HTTP/HTTPS, TCP/IP, IPv4/IPv6, RTSP, UDP, NTP, DHCP, DNS, IP Filter, DDNS, IP Search, ONVIF 2.4, SDK, CGI

DC12V/4A

&lt;3W (without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

375mm x 281.5mm x 56mm

1.6kg (without HDD)