

CP- UNR-4K4082-V2**8 Ch. 4K Network Video Recorder****Main Features**

- Up to 8 channel IP camera input
- Instastream/H.265/Smart H.264+/H.264
- Up to 8MP resolution preview and playback
- Max 200Mbps Incoming Bandwidth
- Support 2 SATA HDDs up to 10TB Each, 2 USB(1 USB3.0)
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras
- ONVIF Version 2.4 conformance
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro



CP- UNR-4K4082-V2

8 Ch. 4K Network Video Recorder

Feature

Processor

IP Camera Input

Operating System

Two-way Talk

User Interface

Video Output

Compression

Video Resolution

Video Recording

Decoding Capacity

Recording Resolution

Video Display Split

Motion Detection

Video Loss

Camera Blank

Alarm Input

Alarm Output

Hard Disk

Smart Phone

Trigger Events

Recording Mode

Search Mode

Playback Function

Backup Mode

Specification

Dual-core embedded processor

8 channel

Embedded LINUX

1 channel Input, 1 channel Output, RCA

GUI

1 HDMI, 1 VGA

Instastream/H.265/Smart H.264+/H.264

HDMI: 3840×2160, 1920×1080, 1280×1024, 1280×720
VGA: 1920×1080, 1280×1024, 1280×720

200 Mbps

8 channels@1080P(30fps)

8MP/ 6MP/ 5MP/ 4MP/ 3MP/ 1080P/ 1.3MP/ 720P etc

1/4/8/9

MD Zones: 396(22×18).

Supports

Supports

4 Channel

2 Channel

2 SATA III ports, up to 10TB Each

iPhone, iPad, Android Phone

Recording, PTZ, Tour, Video Push, Email, Snapshot, Buzzer & Screen tips

Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Tampering, Video Loss), Stop

Time/Date, Alarm, MD & Exact search (accurate to second), Smart search

Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom

USB Device/Network

CP- UNR-4K4082-V2

8 Ch. 4K Network Video Recorder

Feature

Interface Ports

Max Remote Access

Record Interval

Ethernet

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

2 USB Ports (1 USB2.0, 1 USB3.0)

128 users

1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec

1 RJ-45 port (10/100M/1000Mbps)

HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, IGMP, ARP, SSL, ANR, RTP, QoS, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, SNMP, FTP, IP Search, ONVIF 2.4, SDK, CGI Conformant

DC12V/4A

<6.9W (Without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

375mm x 281.5mm x 56mm

1.6kg (without HDD)