

CP- UNR-4K4164-V2**16Ch. H.265+ 4K Network Video Recorder****Main Features**

- Up to 16 channel IP camera input
- Smart H.265+/H.265/Smart H.264+/H.264
- Up to 8MP resolution preview and playback
- Max 200Mbps incoming bandwidth
- Support 4 SATA HDDs up to 10TB Each, 2 USB(1 USB3.0)
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras
- Supports SDK
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro



CP- UNR-4K4164-V2

16Ch. H.265+ 4K Network Video Recorder

Feature

Processor
 IP Camera Input
 Operating System
 Two-way Talk
 User Interface
 Video Output
 Compression
 Video Resolution
 Video Recording
 Video Display Split
 Motion Detection
 Video Loss
 Camera Blank
 Alarm Input
 Alarm Output
 Hard Disk
 Smart Phone
 Trigger Events
 Recording Mode
 Search Mode
 Playback
 Backup Mode
 Interface Ports
 Max User Account
 Record Interval
 Ethernet
 Protocols

Specification

Quad-core embedded processor
 16 channel
 Embedded LINUX
 1 channel Input, 1 channel Output, RCA
 GUI
 1 HDMI, 1 VGA
 Smart H.265+/H.265/Smart H.264+/H.264
 HDMI: 3840×2160, 1920×1080, 1280×1024, 1280×720
 VGA: 1920×1080, 1280×1024, 1280×720
 Max 200Mbps
 1/4/8/9/16
 MD Zones: 396(22×18).
 Supports
 Supports
 16 Channel, Low Level Effective, Green Terminal Interface
 4 Channel, NO/NC Programmable, Green Terminal Interface
 4 SATA ports, up to 10TB Each
 iPhone, iPad, Android Phone
 Recording, PTZ, Tour, Alarm out, Video Push, Email, FTP, Snapshot, Buzzer & Screen tips
 Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Tampering, Video Loss), Stop
 Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
 Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
 USB Device/Network
 2 USB Ports (1USB 3.0), 1 RS485, 1 RS232
 128 users
 1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
 2 RJ-45 10/100/1000 Mbps self-adaptive Ethernet ports
 HTTP; HTTPS; TCP/IP; IPv4/IPv6; UPnP; SNMP; RTSP; UDP; SMTP; NTP; DHCP; DNS; IP Filter; DDNS; FTP; Alarm Server; IP Search ; ONVIF (profile T/S/G); CGI; SDK



CP- UNR-4K4164-V2**16Ch. H.265+ 4K Network Video Recorder****Feature**

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

AC 100~240V, 50/60 Hz

<13.7W (Without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

440mm x 411.1mm x 76mm

4.7kg (without HDD)