

CP-ANW-GPM24G4F4-N40

24 Port Gigabit + 4 Port Gigabit SFP Layer 2 Managed PoE Switch

- Supports IEEE 802.3i, IEEE 802.3u, IEEE802.3ab, IEEE802.3z, IEEE802.3x, IEEE802.3at, IEEE802.3af, IEEE802.3az.
- 24 x Gigabit PoE+ Ports and 4 x Gigabit Combo.
- Supports MAC address auto learning and auto aging.
- Store and forward mode operates.
- Supports PoE power up to 30W for each PoE Port, all power up to 400W.
- LED indicators for monitoring power, link/activity.
- Support QoS, port mirroring, link aggregation protocol.
- 19 inches full metal iron shell and internal power adapter design, suitable for rack installation.



System Overview

As most of the CP PLUS products have been integrated with the Power of Ethernet technology which makes troubleshooting easier in case any errors occur. This can be done with the help of a PoE Switch makes increases reliability rapidly.

Functions

Higher Bandwidth

4 Gigabit SFP (Combo) Uplink Port for higher bandwidth connections. Long distance power supply with a power budget of 400 watts .



CP-ANW-GPM24G4F4-N40

24 Port Gigabit + 4 Port Gigabit SFP Layer 2 Managed PoE Switch

Functions

Better Connectivity

This PoE Switch has designed for outstanding power with flexible placement for better and advanced connectivity between network devices.

Switching Performance

This PoE Switch offers the forwarding capacity to simultaneously process traffic on all ports at line rate without any packet loss.

Easy to Use

This PoE Switch is quite easy to install and use. It requires no configuration and installation. With outstanding performance and quality, this AI PoE Switch is a great selection for expanding your home or workplace network.

About CP PLUS

The brand that is on its way to lead the world when it comes to the security and surveillance industry, CP PLUS, keeps bombarding the market with the most reliable range of products that have been designed carefully and methodically to automate the whole surveillance and security process, no matter how big your premises are.

It was the initiative to help the public in the area where they are the most vulnerable and to empower the sense of safety in our hearts that had conceptualized CP PLUS. And embarking on its mission to make the world a safer and more secure place has taken the brand's journey to unprecedented levels even when compared to international competitors.



CP-ANW-GPM24G4F4-N40

24 Port Gigabit + 4 Port Gigabit SFP Layer 2 Managed PoE Switch

Feature	Specification
Network Port	24 x 10/100/1000Mbps ports 4 x 1000Mbps Combo ports 1 x Console port
Network Standard	IEEE 802.3i, IEEE 802.3u, IEEE802.3ab, IEEE802.3x, IEEE802.3az, IEEE802.3af, IEEE802.3at
Network Media (Cable)	10Base-T: UTP category 3, 4, 5 cable (maximum 100m) 100Base-Tx: UTP category 5, 5e cable (maximum 100m) 1000Base-T: UTP category 5e, 6 cable (maximum 100m) 1000Base-X: MMF, SMF
Transfer Method	Store-and-Forward
MAC Address Table	8K
Switching Capacity	56Gbps
Packet Forwarding Rate	41.67Mpps
Packet Buffer	4.1Mbit
Jumbo Frame	12K Bytes
PoE Ports (RJ45)	24 x PoE ports compliant with 802.3at/af
Power Pin Assignment	1/2(+), 3/6(-)
Indicator	Power, System (Per Device); Link/Activity (Per Port)
Power Budget	400W@100~260VAC, 50/60HZ
Power Input	100~240V AC, 50/60HZ
Power Consumption	Maximum (PoE on): 400W
Operating Temperature	0°C ~45°C

THINK SECURITY
THINK CP PLUS



Feature	Specification
Working Humidity	10%~90% (Non-condensing)
Storage Temperature	-40°C ~70°C
Storage Humidity	5%~90% (Non-condensing)
Dimensions	440mm(W) x 290mm(D) x 44.5mm(H)



**Product casing and specifications are subject to change without prior notice*

Software Specification

L2 Features		Support
MAC Address Table		8K
Jumbo Frame		10K (10000)
Flow Control	802.3x (Full-duplex)	Yes
	Back-Pressure (Half-duplex)	Yes
Spanning Tree	IEEE 802.1D (STP)	Yes
	IEEE 802.1w (RSTP)	Yes
	IEEE 802.1s (MSTP)	16 instances
	Auto Edge Port	Yes
	BPDU Filtering	Yes
	ERPS	Yes
	Self Loop Detection	Yes
Link Aggregation	IEEE 802.3ad LACP	Yes
	Static Trunk	Yes
	Max. Group	8
	Max. Ports/Group	8
	Traffic Load Balancing	Yes
L2 Features		
Static Routing		Yes (IPv4/IPv6)
Address Resolution Protocol (ARP)	Static ARP	Yes
VLAN		
VLAN	Static VLAN	256
	Port-based	Yes
	IEEE 802.1Q Tagged-based	Yes
	Protocol-based	8 groups
	MAC-based	256
Voice VLAN	OUI Mode (Auto/Manual)	16 OUI
Surveillance VLAN	OUI Mode (Auto/Manual)	16 OUI
QinQ (IEEE 802.1ad)	Basic	Yes
GARP VLAN Registration Protocol (GVRP)		Yes

Multicast		
Common	Multicast Groups	256
	Immediate Leave	Yes
	Static/Forbidden Router Port	Yes
	Static/Forbidden Forward Port	Yes
	Filtering	128 profiles
	Throttling	Yes
IGMP Snooping	IGMP v1/v2	Yes
	IGMP v3 Basic (BISS)	Yes
	IGMP v2/v3 Querier	Yes
MLD Snooping	MLD v1/v2	Yes
Multicast VLAN Registration (MVR)		Yes (IPv4)
QoS Features		
Priority Queue		8 queues/port
Queue Scheduling	WRR	Yes
	WFQ	Yes
	Strict Priority	Yes
	Hybrid(WRR+SP or WFQ+SP)	Yes
Class of Service	Port-based	Yes
	802.1p	Yes
	IP TOS Precedence	Yes
	IP DSCP	Yes
Trusted QoS		Yes
Rate Limit	Port-based (Ingress/Egress)	Yes
Access Control List (ACL)		
Access Rules		1024
ACL Type	L2/L3/L4	Yes
	MAC-based	512
	IPv4-based	
	IPv6-based	
PoE Function	Power	Yes
	Current	Yes
	Voltage	Yes
	PoE Watch Dog	Yes

Security		
AAA	Authentication	Yes
TACACS+		8
RADIUS		8
Authentication Manager	IEEE 802.1X	Yes
	MAC Auth	Yes
	Web Auth	Yes
	Guest VLAN	Yes
	Port-based	Yes
	Host-based	Yes
Account Manager	Local Authenticoin	Yes
	Multiple User Account	8
	Multi-Level Security (Manager/Operator)	Yes
	Password Recovery Procedures	Yes
Management Access	Management VLAN	Yes
	Management ACL	256
SSL	SSLv2	Yes
	SSLv3	Yes
	TLSv1	Yes
WebUI	HTTPS	Yes
CLI	SSH v1/v2	Yes
Port Security	Dynamic Lock	256
Storm Control	Broadcast	Yes
	Unknown Multicast	Yes
	Unknown Unicast	Yes
Spanning Tree	BPDU Guard	Yes
Protected Port (Port Isolation)		Yes
Black Hole MAC		Yes
CPU Defence Engine		Yes
DoS Prevention		Yes
DHCP Snooping (with Option 82)		Yes
Dynamic ARP Inspection		Yes
IP Source Guard		256
IP/MAC/Port Binding (IMPB)		Yes
Dynamic VLAN Assignment		Yes

IPv6		
IPv6 Host	Auto Configuration	Yes
	Static IPv6 Address and Prefix Length	Yes
	Static IPv6 Default Gateway	Yes
	IPv6 Neighbor Discovery (ND)	Yes
	IPv6 Duplicate Address Detection	Yes
	ICMPv6	Yes
IPv6 Application	HTTP/HTTPS	Yes
	TELNET	Yes
	SSH	Yes
	SNMP	Yes
	TFTP	Yes
	Syslog	Yes
	PING	Yes
	DHCPv6	Yes
Management		
CLI	Console	3 sessions
	Telnet (RFC854)	
WebUI	HTTP	Yes
SNMP	v1	Yes
	v2c	Yes
	v3	Yes
File Management	Firmware Upgrade/Backup	Yes
	Dual Images	Yes
	Configuration Download/Backup	Yes
	Multiple Configurations	Yes
Upload/Download	TFTP (RFC783)	Yes
	HTTP	Yes
	JART	Yes
Time Management	Local	Yes
	SNTP	Yes
Port Management	Friendly Port Name (Port Description)	Yes
	Error Disabled Recovery	Yes
Line Management	Console	Yes
	Telnet (RFC854)	Yes
	SSH v1/v2	Yes
DHCP	Client	Yes
DNS	Client	Yes
Software Reset Button		Yes
EEE (802.3az)		Yes
RMON Management		32 entries / type

Discovery		
IEEE 802.1AB Link Layer Discovery Protocol (LLDP)		Yes
ANSI/TIA-1057 LLDP Media Endpoint Discovery (LLDP-MED)		Yes
Diagnostics		
Mirroring	Port-based (Many to One)	4 sessions
Syslog (RFC3164)	Local RAM	Yes
	Local Flash	Yes
	Remote Server	8
System Diagnostics	CPU Utilization	Yes
	Memory Utilization	Yes
	Port Utilization	Yes
	Technical Support Log	Yes
Port Diagnostics	Cable Test	Yes
	Fiber Module Status	Yes
Network Diagnostics	Ping Test	Yes
	Traceroute	Yes
UDLD		Yes
MIB		
RFC1213 MIBII (System & Interface groups)		Yes
RFC2819 RMON I (1,2,3, & 9 groups)		Yes
RFC1215 Generic Traps		Yes
RFC1493 Bridge		Yes
RFC2674 Bridge MIB Extensions		Yes
RFC2737 Entity		Yes
RFC3635 Ethernet-Like		Yes
RFC2863 Interface Group		Yes
SNMP-Community-MIB		Yes
SNMPv3-MIB		Yes