



JARVIS U2

PTZ AUTO ROTATE VOICE
TRACKING CAMERA

Applications: Conference room | Hybrid class room



FULL HD
1080 P




12X ZOOM



4 MIC ARRAY



VOICE TRACKING



USB & HDMI



MAKE IN INDIA



JARVIS U2

SPECIFICATION



Camera	
Image Sensor	1/2.8inch CMOS
Min Lux	0.1Lux(F1.2)
Effective Pixel	2.2 MP
Optical Zoom	12X
Digital Zoom	4X/12X
Shutter Speed	1 to 1/10000s
Field of View	72.5°
Frame Rate	1920×1080,1280×720, 640×480
Focus Mode	Auto
Aperture Mode	Auto
Backlight Compensation	Support
Wide Dynamic	Support
Picture Adjustment	Brightness, Chroma, Saturation, Contrast, Acutance

Microphone	
MIC Array Quantity	4
MIC Array Form	linear
Sampling Rate	16KHz/48KHz
Sensitivity	-26dBfs
Far-field Pick up Voice Distance	Up to 20ft
Horizontal Voice Pick up Angle	Horizontal 180°
SNR	65.5dB
Communication Mode	Full duplex

Interface	
Video Interface	USB 3.0 Type-B, HDMI
Video Compressed Format	MJPG/H.264
Control Interface	RS-232, USB2.0
Control Agreement	VISCA/PELCO-D/PELCO-P
Communicate Baud Rate	2400/4800/9600/11520/19200/38400
Power Interface	(DC12V)

PTZ	
Pan Rotation	-170°~ +170°
Tilt Rotation	-30°~ +90°
Horizontal Rotate Speed	0.1~100°/second
Vertical Rotate Speed	0.1~80° / second

Others	
Power Adapter	DC12V/2A
Decoder	Built in
Input voltage	DV12V
Power Consumption	12W (MAX)
Storage Temperature	-10°C ~ +60°C / 20% ~ 95%
Working temperature	-10°C ~ +50°C / 20% ~ 80%
Operating Environment	Indoor
Size	180*180*172mm
Weight	1360g

*OPTIONAL ACCESSORIES - WALL MOUNT, CEILING MOUNT, CABLES

+91 452 4392222

sales@atnetindia.net

www.atnetindia.net