

Revel F328Be

3-way Triple 8" Floorstanding Loudspeaker

REVEL®

PERFORMA⁴ Be™



Highlights:

- Flagship floorstander for the PerformaBe range
- 1-inch Beryllium Dome Tweeter
- 6th-generation Acoustic Lens Waveguide
- Deep Ceramic Composite (DCC) Cone Midrange and Woofers
- High-order Crossovers with Film Capacitors and Air Core Inductors
- Magnetically Attached Grilles
- 4 Premium high-gloss finishes available

Specifications:

Type	3-way triple 8" floorstanding loudspeaker
Low-frequency transducer	Three 8" (200mm) Deep Ceramic Composite aluminum cones, with cast frames
Midrange transducer	5-1/4" (130mm) Deep Ceramic Composite aluminum cone, with cast frame
High-frequency transducer	1" (25mm) Beryllium dome, with acoustic lens waveguide
Recommended amplifier power range	50 – 400 Watts
Frequency response	26Hz – 40kHz (-6dB)
Low-frequency extension	24Hz (-10dB); 26Hz (-6dB); 35Hz (-3dB)
Nominal impedance	8 ohms
Sensitivity (2.83V/1m)	91dB
Crossover frequencies	240Hz; 2.1kHz
Enclosure type	Bass-reflex via dual rear-mounted ports
Inputs	Dual gold-plated binding posts with shorting straps
Available high-gloss finishes	Black, White, Metallic Silver, and Walnut
Dimensions with grille and base (H x W x D)	50.9" x 13.5" x 17.6" (1294mm x 341.3mm x 448.5mm)
Product Weight	112.6 lb (51.0kg)

Revel F328Be

3-way Triple 8" Floorstanding Loudspeaker

REVEL®

PERFORMA⁴ Be

