Revel F226Be 3-way Dual 6.5" Floorstanding Loudspeaker







Highlights:

- 1-inch Beryllium Dome Tweeter
- 5th-generation Acoustic Lens Waveguide
- Deep Ceramic Composite (DCC) Cone Midrange and Woofers
- High-order Crossovers with Film Capacitors and Air Core Inductors
- Magnetically Attached Grille
- 4 Premium high-gloss finishes available

Specifications:

| Туре | 3-way dual 6.5" floorstanding loudspeaker |
|---|--|
| Low-frequency transducer | Two 6.5" (165mm) Deep Ceramic Composite aluminum cones, with cast frames |
| Midrange transducer | 5-1/4" (130mm) Deep Ceramic Composite aluminum cone, with cast frame |
| High-frequency transducer | 1" (25mm) Beryllium dome, with acoustic lens waveguide |
| Recommended amplifier power range | 50 – 200 watts |
| Frequency response | 44Hz — 40kHz (-6dB) |
| Low-frequency extension | 38Hz (-10dB); 44Hz (-6dB); 50Hz (-3dB) |
| Nominal impedance | 8 ohms |
| Sensitivity (2.83V/1m) | 90dB |
| Crossover frequencies | 260Hz; 2.1kHz |
| Enclosure type | Bass-reflex via front-mounted port |
| Inputs | Dual gold-plated binding posts with shorting straps |
| Available high-gloss finishes | Black, White, Metallic Silver, and Walnut |
| Dimensions – with grille (H x W x D) | 41.3" x 9.8" x 13.7" (1050mm x 249mm x 347mm) |
| Product Weight: | Cabinet Weight: 58.0 lb (26.4kg) Grille Weight: 0.8 lb (0.4kg) |











