


# PLATINUM - A

LFSL1091A,B,C,D,E

## RECESSED MODULAR SPOTLIGHT



### Accessories



Honeycomb



Beam Soft



White



Titanium



Matt Silver

### Reflector




Outer Ring



Retrofit

Wattage (W)		7W	9W	12W	15W	18W	24W	33W	40W
LUMEN OUTPUT	N 4000K	720	900	1262	1485	1634	2639	3128	4048
	W 3000K	672	840	1262	1485	1634	2500	2924	3784
	W 2700K	672	840	1173	1380	1518	2399	2720	3520
SYSTEM EFFICIENCY	No. of LEDs	1	1	1	1	1	1	1	1
	THD (%)	-	20	20	20	20	15	15	20
	Power Factor	>0.45	>0.9	>0.9	>0.9	>0.9	>0.95	>0.95	>0.95
	Driver Rating	36V DC 150mA	36V DC 200mA	36V DC 300mA	36V DC 350mA	36V DC 400mA	36V DC 600mA	36V DC 700mA	36V DC 1000mA
DIMENSIONS (in mm)	Diameter X	85	85	85	85	115	115	140	165
	Height H	89	89	89	89	140	140	169	184
	Cutout Ø	75	75	75	75	100	100	125	150

SYSTEM SPECS	Housing	Aluminium
	LED Make	Cree
	Driver Brand	Fulham
	Dimming	Triac / Analog / Dali
BEAM ANGLES	7W, 9W, 12W, 15W	18° 36° 50°
	18W, 24W, 33W, 40W	15° 24° 38° 55°
COLOUR OPTIONS	Housing	White Black
	Reflector	Titanium Matt Silver White



CRI	TEMP	IP RATING	INPUT
80 / 90	0-45°	IP-20	240V/ 50Hz