

ANGEL PLUS

LFSL1122A

LINEAR SPOT LIGHT



Accessories



Honeycomb



Wattage (W)		5W	10W	15W	20W	
LUMEN OUTPUT	N 4000K	460	920	1380	1840	
	W 3000K	450	900	1350	1800	
SYSTEM EFFICIENCY	No. of LEDs	2	4	6	9	
	THD (%)	-	60	60	≤15	
	Power Factor	0.5	0.85	0.85	0.95	
	Driver Rating	2.8-9V 700mA	7-12V 700mA	12-21V 700mA	20-40V 700mA	
	URG Rating	<16	<16	<16	<16	
	Surge	1.5kV	2.5kV	3kV	2kV	
DIMENSIONS (in mm)	Size	L 90 W 67	L 150 W 67	L 210 W 67	L 300 W 67	
	Height	H 50	H 50	H 50	H 50	
	Cutout	L	83	143	203	293
		W	57	57	57	57

SYSTEM SPECS	Housing	Aluminum
LED Make	Osram	
Driver Brand	Alloking (5W), Fulham (10W,15W,20W)	
Dimming	Triac / Analog(10W,15W,20W) / Dali	

BEAM ANGLES	5W, 10W, 15W, 20W
	15°, 24°, 38°

COLOUR OPTIONS	Housing	White
Reflector	Black	

CRI	TEMP	IP RATING	INPUT
90	0-50°	IP-20	240V/ 50Hz

