


PLATINUM - F

LFSL1096A,B

RECESSED MODULAR SPOTLIGHT



Honeycomb



Beam Soft

Accessories



Outer Ring



Retrofit

Wattage (W)		7W	9W	12W	15W
LUMEN OUTPUT	N 4000K	720	900	1262	1485
	W 3000K	672	840	1262	1485
	W 2700K	672	840	1173	1380
SYSTEM EFFICIENCY	No. of LEDs	1	1	1	1
	THD (%)	-	20	20	20
	Power Factor	>0.45	>0.9	>0.9	>0.9
	Driver Rating	36V DC 150mA	36V DC 200mA	36V DC 300mA	36V DC 350mA
DIMENSIONS (in mm)	Diameter X	85	85	85	85
	Height H	98	98	121	121
	Cutout Ø	75	75	75	75

SYSTEM SPECS	Housing	Aluminium
	LED Make	Cree
	Driver Brand	Fulham
	Dimming	Triac / Analog / Dali

BEAM ANGLES	7W, 9W, 12W, 15W			
		15°	24°	38°

COLOUR OPTIONS	Housing	White	Black
	Reflector	White	

CRI	TEMP	IP RATING	INPUT
80 / 90	0-45°	IP-20	240V/ 50Hz

