


PLATINUM - H

LFSL1098F,A,B

RECESSED MODULAR SPOTLIGHT (OVAL CUT)



Honeycomb

Beam Soft

Accessories



Outer Ring



Retrofit

Slim Fitting

Wattage (W)		7W	9W	7W	9W	12W	15W
LUMEN OUTPUT	N 4000K	720	900	720	900	1262	1485
	W 3000K	672	840	672	840	1262	1485
	W 2700K	672	840	672	840	1173	1380
SYSTEM EFFICIENCY	No. of LEDs	1	1	1	1	1	1
	THD (%)	20	20	-	20	20	20
	Power Factor	>0.9	>0.9	>0.45	>0.9	>0.9	>0.9
	Driver Rating	36V DC 150mA	36V DC 200mA	36V DC 150mA	36V DC 200mA	36V DC 300mA	36V DC 350mA
DIMENSIONS (in mm)	Diameter X	65	65	75	75	75	75
	Height H	79	79	91	91	114	114
	Cutout Ø	55	55	65	65	65	65

SYSTEM SPECS	Housing	Aluminium
LED Make	Cree	
Driver Brand	Fulham	
Dimming	Triac / Analog / Dali	

BEAM ANGLES	7W, 9W, 12W, 15W
	15° 24° 38° 55°

COLOUR OPTIONS	Housing	White
	Reflector	White

CRI	TEMP	IP RATING	INPUT
80 / 90	0-45°	IP-20	240V/ 50Hz

