

PLATINUM - I

LFSL1099A,B

RECESSED MODULAR SPOTLIGHT (WALL WASHER)




Honeycomb



Beam Soft

Accessories



Outer Ring



Retrofit

| | | Wattage (W) | | | |
|--------------------|---------------|-----------------|-----------------|-----------------|-----------------|
| | | 7W | 9W | 12W | 15W |
| LUMEN OUTPUT | N 4000K | 720 | 900 | 1262 | 1485 |
| | W 3000K | 672 | 840 | 1262 | 1485 |
| | W 2700K | 672 | 840 | 1173 | 1380 |
| SYSTEM EFFICIENCY | No. of LEDs | 1 | 1 | 1 | 1 |
| | THD (%) | - | 20 | 20 | 20 |
| | Power Factor | >0.45 | >0.9 | >0.9 | >0.9 |
| | Driver Rating | 36V DC 150mA | 36V DC 200mA | 36V DC 300mA | 36V DC 350mA |
| DIMENSIONS (in mm) | Diameter X | 88 | 88 | 88 | 88 |
| | Height H | 88 | 88 | 109 | 109 |
| | Cutout Ø | 75 | 75 | 75 | 75 |

| | | |
|--------------|--------------|-----------------------|
| SYSTEM SPECS | Housing | Aluminium |
| | LED Make | Cree |
| | Driver Brand | Fulham |
| | Dimming | Triac / Analog / Dali |

| | | | | |
|-------------|------------------|-----|-----|-----|
| BEAM ANGLES | 7W, 9W, 12W, 15W | | | |
| | 15° | 24° | 38° | 55° |

| | | | |
|----------------|---------|-------|-------|
| COLOUR OPTIONS | Housing | White | Black |
|----------------|---------|-------|-------|

| | | | |
|---------|-------|-----------|---------------|
| CRI | TEMP | IP RATING | INPUT |
| 80 / 90 | 0-45° | IP-20 | 240V/ 50Hz |

