

# PLATINUM - L

LFGL1102A,B,C,D,E

## RECESSED MODULAR GIMBLE LIGHT



Outer Ring



Retrofit

Wattage (W)		14W	18W	24W	30W	36W	48W	66W	
LUMEN OUTPUT	N 4000K	1440	1800	2524	2970	3268	5278	6256	
	W 3000K	1345	1680	2524	2970	3268	5000	5848	
	Y 2700K	1345	1680	2345	2760	3036	4798	5440	
SYSTEM EFFICIENCY	No. of LEDs	1	1	1	1	1	1	1	
	THD (%)	-	20	20	20	20	15	15	
	Power Factor	>0.45	>0.9	>0.9	>0.9	>0.9	>0.95	>0.95	
	Driver Rating	36V DC 150mA x2	36V DC 200mA x2	36V DC 300mA x2	36V DC 350mA x2	36V DC 400mA x2	36V DC 600mA x2	36V DC 700mA x2	
DIMENSIONS (in mm)	Size	L	175	175	175	175	220	220	260
		W	90	90	90	90	110	110	130
	Height	H	79	79	102	102	116	116	139
		Cutout	L	165	165	165	165	205	205
W	80		80	80	80	95	95	115	

SYSTEM SPECS	Housing	Aluminium		
	LED Make	Cree		
	Driver Brand	Fulham		
	Dimming	Triac / Analog / Dali		
BEAM ANGLES	14W, 18W, 24W, 30W, 36W, 48W, 66W			
	15°	24°	38°	55°
COLOUR OPTIONS	Housing	<input type="checkbox"/> White <input type="checkbox"/> Black		
CRI	TEMP	IP RATING	INPUT	
80 / 90	0-45°	IP-20	240V/ 50Hz	

