


# RADIUS


LFDL1077R

## RECESSED FIXED DOWNLIGHT



Wattage (W)		7W	10W	12W	15W	20W	25W	30W	35W
LUMEN OUTPUT	C 6500K	734	979	1468	1713	2448	2937	3672	4161
	N 4000K	734	979	1468	1713	2448	2937	3672	4161
	W 3000K	707	943	1414	1650	2358	2829	3537	4008
SYSTEM EFFICIENCY	No. of LEDs	36	36	48	48	96	96	144	144
	THD (%)	-	20	20	20	20	15	15	15
	Power Factor	>0.5	>0.9	>0.9	>0.9	>0.9	>0.95	>0.95	>0.95
	Driver Rating	27-40V DC 150mA	23-45V DC 200mA	22-44V DC 300mA	26-36V DC 350mA	20-40V DC 500mA	25-50V DC 600mA	37V DC 750mA	37V DC 850mA
	Surge	2kV	2kV	2kV	2kV	2kV	2kV	2kV	2kV
DIMENSIONS (in mm)	Diameter X	78	78	103	103	153	153	211	211
	Height H	55	55	58	58	58	58	58	58
	Cutout Ø	72	72	98	98	148	148	206	206

SYSTEM SPECS	Housing	Aluminum
LED Make	Bridgelux	
Driver Brand	Fulham	
Dimming	Triac / Analog / Dali	



BEAM ANGLES	7W,10W,12W,15W,20W,25W,30W,35W
	90°

CRI	TEMP	IP RATING	INPUT
80	0-50°	IP-20	240V/ 50Hz